Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-761-6054

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and	275.0 degrees fahrenheit single response
Outside Diameter:	
0.516 inches	
Minimum Inside Bending R	adius:
3.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st er	ıd
Thready Qty Per Inch (tpi):	
20 1st end	
Burst Test Pressure:	
12000.0 pounds per square i	nch
Layer Composition And Lo	cation:
1st layer braided cotton cord	and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Press	ıre:
3000.0 pounds per square in	ch
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Vacuum In Torr:	
50.8	
Inside Surface Condition:	
Smooth	
Measuring Method And Ler	igth:
213.500 inches working	
Media For Which Designed	<u>.</u>
Air and fuel/oil, hydrocarbor	
Thread Series Designator:	
Unf 1st end	

## NSN 4720-00-761-6054

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

