NSN 4720-00-762-0109

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-762-0109

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| Between 0.204 inches and 0.234 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| Between 0.418 inches and 0.461 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 6000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 37.000 inches working |
| Media For Which Designed: |

Fuel/oil, hydrocarbon single response

NSN 4720-00-762-0109

Nonmetallic Hose Assembly - Page 2 of 2



| Th. | | Carias | Dagian | 4 |
|-------|-----|--------|--------|--------|
| 11116 | tau | Series | Design | iatoi. |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0