NSN 4720-00-762-8862

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-762-8862	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.212 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	
Outside Diameter:	
0.400 inches	
Minimum Inside Bending Radius:	
1.500 inches	
Exterior Color:	
Natural	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

Outer Covering Environmental Protection:

9.750 inches

NSN 4720-00-762-8862

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjf 1st end
Specification Data:
81349-mil-h-38360 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A542a0

Mil-std (military Standard):

Mil-h-38360 spec.