Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-763-3090

Cross Sectional	onape:
Round	
Thread Class:	
2b 1st end	
Thread Direction	
Right-hand 1st en	d
Inside Diameter:	
0.406 inches	
Tempurature Rat	ting:
-40.0 degrees fah	renheit and 275.0 degrees fahrenheit single response
Outside Diamete	r:
0.766 inches	
Minimum Inside	Bending Radius:
4.620 inches	
Connection Style	9:
Swivel nut flare 1	st end
End Connection	Design:
Straight 1st end	
Connection Type):
Threaded internal	tube 1st end
Thready Qty Per	Inch (tpi):
16 1st end	
Burst Test Press	ure:
8000.0 pounds pe	er square inch
Layer Compositi	on And Location:
1st layer braided	cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Opera	ting Pressure:
2000.0 pounds pe	er square inch
Thread Size:	
0.750 inches 1st	end
Seat Angle:	
37.0 degrees 1st	end
Vacuum In Torr:	
50.8	
Inside Surface C	ondition:
Smooth	
Measuring Metho	od And Length:
91.281 inches wo	orking
Media For Which	Designed:
	ydrocarbon single response
Thread Series De	
Unf 1st end	-

NSN 4720-00-763-3090

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

