NSN 4720-00-763-3124

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-763-3124

| Cross Sectional Shape: |
|---|
| Round |
| |
| Thread Class: |
| 2b 1st end Thread Directions |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.188 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.516 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Vacuum In Torr: |
| 50.8 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 28.625 inches working |
| Media For Which Designed: |
| Air and fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |

N/a

NSN 4720-00-763-3124

Nonmetallic Hose Assembly - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0