## NSN 4720-00-763-5982

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-763-5982

Cross Sectional Shape
Cross Sectional Shape:
Round
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response  Outside Diameter:
Between 0.367 inches and 0.406 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural Connection Style:
Connection Style:  Swivel nut flare 1st end
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability  Second End Bolotionship With First End.
Second End Relationship With First End:
Identical  Burst Test Pressure:
6500.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:  Outer lever breided corrector reciptant steel wire
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Heat resistant  Inside Surface Condition:
Smooth  Magazing Method And Longth:
Measuring Method And Length:
55.000 inches working  Media For Which Designed:
Media For Which Designed:  Alcohol, ethyl, and alcohol, methyl, and fuel/oil, hydrocarbon, and hydraulic fluid, and fuel/oil, hydrocarbon, and water single response.
Alcohol, ethyl and alcohol, methyl and fuel/oil, hydrocarbon and hydraulic fluid and fuel/oil, hydrocarbon and water single response
Shelf Life:

## NSN 4720-00-763-5982

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0