NSN 4720-00-764-5271

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-764-5271

Cross Sectional Shape:						
Round						
Thread Class:						
3b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.500 inches						
Outside Diameter:						
1.155 inches						
Minimum Inside Bending Radius:						
6.000 inches						
Inner Conveying Tube Style:						
Annular close-pitch corrugated						
Connection Style:						
Swivel nut, flareless 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Features Provided:						
Identical ends						
Burst Test Pressure:						
9000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire						
Maximum Operating Pressure:						
Maximum Operating Pressure:						
Maximum Operating Pressure: 2200.0 pounds per square inch						
. •						
2200.0 pounds per square inch						
2200.0 pounds per square inch Thread Size:						
2200.0 pounds per square inch Thread Size: 0.750 inches 1st end						
2200.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle:						
2200.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 12.0 degrees 1st end						
2200.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure:						
2200.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch						
2200.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection:						
2200.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant						
2200.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length:						
2200.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length: 36.000 inches						
2200.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length: 36.000 inches Thread Series Designator:						

NSN 4720-00-764-5271

Metallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0