Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-764-7344

	iew Online at https://aerobasegroup.com/nsn/4720-00-764-7344
С	ross Sectional Shape:
R	ound
Т	hread Class:
Зł	o 1st end
Т	hread Direction:
R	ight-hand 1st end
In	side Diameter:
0.	312 inches
Te	empurature Rating:
-6	7.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
0	utside Diameter:
0.	446 inches
Μ	inimum Inside Bending Radius:
4.	000 inches
C	onnection Style:
S	wivel nut flare 1st end
E	nd Connection Design:
St	traight 1st end
C	onnection Type:
Tł	hreaded internal tube 1st end
Fe	eatures Provided:
EI	lectrostatic discharge capability
В	urst Test Pressure:
90	000.0 pounds per square inch
La	ayer Composition And Location:
0	uter layer braided corrosion resistant steel wire
М	aximum Operating Pressure:
15	500.0 pounds per square inch
TI	hread Size:
0.	562 inches 1st end
S	eat Angle:
37	7.0 degrees 1st end
H	ydrostatic Test Pressure:
30	000.0 pounds per square inch
Va	acuum In Torr:
50	0.8
In	side Surface Condition:
Si	mooth
М	easuring Method And Length:
	1.000 inches working
	hread Series Designator:
U	nf 1st end

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Specification Data:

96906-ms8005 government standard

Specification Or Standard:

1 class and 6 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.