Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-765-3413

Cro	oss Sectional Shape:
Rou	und
Thr	ead Class:
3b	1st end
Thr	ead Direction:
Rig	ht-hand 1st end
Ins	ide Diameter:
0.18	88 inches
Ter	npurature Rating:
-65	0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Out	tside Diameter:
0.3	12 inches
Со	nnection Style:
Swi	vel nut flare 1st end
End	d Connection Design:
Stra	aight 1st end
Со	nnection Type:
Thr	eaded internal tube 1st end
Fea	tures Provided:
Ele	ctrostatic discharge capability
Bu	rst Test Pressure:
120	00.0 pounds per square inch
Lay	ver Composition And Location:
Out	er layer braided corrosion resistant steel wire
Ma	ximum Operating Pressure:
100	0.0 pounds per square inch
Thr	ead Size:
0.43	38 inches 1st end
Sea	at Angle:
37.0	0 degrees 1st end
Ins	ide Surface Condition:
Sm	ooth
Mea	asuring Method And Length:
13.	250 inches working
Thr	ead Series Designator:
Unf	1st end
She	elf Life:
N/a	
Uni	t Of Measure:
Der	nilitarization:
No	

NSN 4720-00-765-3413

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

