## NSN 4720-00-765-3414

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-765-3414 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.312 inches **Minimum Inside Bending Radius:** 2.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch **Outer Covering Environmental Protection:** Corrosion resistant **Vacuum In Torr:** 50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 20.750 inches working

**Thread Series Designator:** 

Unf 1st end

## NSN 4720-00-765-3414

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0