## NSN 4720-00-765-4890

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-765-4890

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 158.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber,
chloroprene
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and hydraulic solution resistant and mildew resistant and oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
29.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response

Unjf 1st end

**Thread Series Designator:** 

## NSN 4720-00-765-4890

Nonmetallic Hose Assembly - Page 2 of 2



	Sı	peci	fica	tion	Data
--	----	------	------	------	------

96906-ms28759e0290 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0