## NSN 4720-00-765-9055

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-765-9055

| Thread Class:   |
|---|
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.875 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 1.094 inches  |
| Minimum Inside Bending Radius:  |
| 7.300 inches  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Elbow 1st end   |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Features Provided:  |
| Electrostatic discharge capability  |
| Thready Qty Per Inch (tpi):   |
| 12 1st end  |
| Burst Test Pressure:  |
| 5000.0 pounds per square inch   |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 1000.0 pounds per square inch   |
| Thread Size:  |
| 1.312 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Flow Angle:   |
| 45.0 degrees 1st end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 31.700 inches working and 32.200 inches working                                       |
| Special Features:   |

Nipple-additional material stainless steel, nipple-additional surface treatment passivated

## NSN 4720-00-765-9055

Nonmetallic Hose Assembly - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
|---------------------------|

Un 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0