

View Online at <https://aerobasegroup.com/nsn/4720-00-766-5871>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.234 inches and 0.281 inches

Outside Diameter:

Between 0.438 inches and 0.484 inches

Exterior Color:

Natural or silver

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

300.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Thread Size:

0.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Abrasion resistant and corrosion resistant and mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.125 inches and 14.750 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Test Data Document:

10001-2282208 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0