NSN 4720-00-766-5877

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-766-5877
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.367 inches and 0.377 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
Between 0.760 inches and 0.781 inches
Exterior Color:
Black or natural
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer molded rubber
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and hydraulic solution resistant and oil resistant and fire resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
50.000 inches and 50.250 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Nntf 1st end

N/a

Shelf Life:

NSN 4720-00-766-5877

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0