Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-766-5877

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
Between 0.367 inches and 0.377 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
Between 0.760 inches and 0.781 inches	
Exterior Color:	
Black or natural	
Connection Style:	
Inverted flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Burst Test Pressure:	
8000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided steel wire and outer layer molded rubber	
Maximum Operating Pressure:	
2000.0 pounds per square inch	
Thread Size:	
0.375 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Hydrostatic Test Pressure:	
4000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Fuel resistant and hydraulic solution resistant and oil resistant and fire resistan	t
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
50.000 inches and 50.250 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Nptf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0