Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-766-9769

Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.875 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit	and 200.0 degrees fahrenheit single response
Outside Diameter:	
1.234 inches	
Minimum Inside Bendir	ng Radius:
7.375 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design	1:
Straight 1st end	
Connection Type:	
Threaded internal tube 1	st end
Features Provided:	
Reusable end fittings	
Thready Qty Per Inch (t	pi):
12 1st end	
Burst Test Pressure:	
500.0 pounds per square	inch
Layer Composition And	Location:
1st layer braided textile y	varn and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pr	essure:
125.0 pounds per square	inch
Thread Size:	
1.312 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Press	ure:
250.0 pounds per square	inch
Outer Covering Environ	imental Protection:
Mildew resistant and oil r	esistant
Vacuum In Torr:	
254.0	

NSN 4720-00-766-9769

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition: Smooth Measuring Method And Length: 27.000 inches Media For Which Designed: Air and fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0