## NSN 4720-00-766-9782

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-766-9782

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.125 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
9.000 inches
Exterior Color:
Black
End Application:
Clark model 290m; tractor, wheeled, ind., diesel driven; med dbp, nsn 2420000889384, w/rops nsn 2420010590090
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
500.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
125.0 pounds per square inch
Thread Size:
1.625 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
250.0 pounds per square inch
Outer Covering Environmental Protection:

Mildew resistant and oil resistant

## NSN 4720-00-766-9782

Nonmetallic Hose Assembly - Page 2 of 2



vacuum in Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
56.500 inches
Media For Which Designed:
Air and fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0