Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-768-9888

Cross Sectio	nal Shape:
Round	
Thread Class	s:
3b 1st end	
Thread Direc	tion:
Right-hand 1s	st end
Inside Diame	ter:
0.485 inches	
Tempurature	Rating:
-65.0 degrees	fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diam	neter:
Between 0.69	0 inches and 0.730 inches
Minimum Ins	ide Bending Radius:
3.250 inches	
Connection S	Style:
Swivel nut flar	re 1st end
End Connect	ion Design:
Straight 1st er	nd
Connection 1	Гуре:
Threaded inte	rnal tube 1st end
Features Pro	vided:
Electrostatic d	lischarge capability and reusable end fittings
Burst Test Pr	ressure:
12000.0 poun	ds per square inch
Layer Compo	osition And Location:
Outer layer br	aided corrosion resistant steel wire
Maximum Op	perating Pressure:
3000.0 pound	s per square inch
Thread Size:	
0.875 inches ²	1st end
Seat Angle:	
37.0 degrees	1st end
Hydrostatic 1	Test Pressure:
6000.0 pound	s per square inch
Outer Coveri	ng Environmental Protection:
Corrosion resi	istant
Inside Surfac	ce Condition:
Smooth	
Measuring M	ethod And Length:
23.000 inches	
Thread Serie	s Designator:
Unjf 1st end	

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:

81343-as153 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0