Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-770-7178

Cross Sectional snape: Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.132 inches Outside Diameter: 0.343 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Thread di Internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrision resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Uter layer braided corrision resistant steel wire Maximum Operating Pressure: 300.0 pounds per square inch Uter layer braided corrision resistant steel wire Maximum Operating Pressure:	Cross Sectional Shaney
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.132 inches Outside Diameter: 0.343 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Portection Type: Threaded internal tube 1st end Features Provided: Izoton pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1300.0 pounds per square inch Stratest 1 1900.0 pounds per square inch Maximum Operating Pressure: 1900.0 pounds per square inch Maximum Operating Pressure: 1900.0 pounds per square inch Uter Corregin St end Hydrogenes 1st end Outer Corregin Pressure:	Cross Sectional Shape:
3b 1st end Thread Direction: Right-hand 1st end Jinside Diameter: 0.132 inches Outside Diameter: 0.343 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Solve In ut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Ostor paise state ad 15000.0 pounds per square inch Hared Size: 12000.0 pounds per square inch Hared Size: 1300.0 pounds per square inch User Same Size: 1300.0 pounds per square inch Hared Size:	
Thread Direction: Right-hand 1st end Inside Diameter: 0.132 inches Outside Diameter: 0.343 inches Outside Diameter: 0.343 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 1st end EndConnection Design: Straight 1st end Connection Type: Threaded linemal tube 1st end Freatures Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Maximum Operating Pressure: 150.0.0 pounds per square inch Hered Size: 0.438 inches 1st end Hydrostatic Test Pressure: 1300.0 pounds per square inch Hydrostatic Test Pressure: 0300.0 pounds per square inch Hydrostatic Test Pressure: 0300.0 pounds per square inch Hydrostatic Test Pressure: 0300.0 pounds per square inch Cuter Covering Environmental Protection: Corrosion resistant Vac	
Right-hand 1st end Inside Diameter: 0.132 inches Outside Diameter: 0.343 inches Minimul Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded Internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 120000 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Strates Maxime Operating Pressure: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Cuter Covering Environmental Protection: Corrosion resistant Hydrostatic Test Pressure: 3000.0 pounds per square inch Duter Covering Environmental Protection: Corrosion resistant Vacum In Tor: Soal Smodh Inside	
Inside Diameter: 0.132 inches Outside Diameter: 0.343 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Corrosion resistant Vacuum In Tor: 50.8 Inside Surface Condition: Smooth Masting Method And Length: 7.000 inches working	
0.132 inches0.343 inchesMinimum Inside Bending Radius:2.000 inchesConnection Style:Switel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchStrades Ist endStrades Ist endMaximum Operating Pressure:0.438 inches 1st endStrades Ist endMurice Test Pressure:0.300.0 pounds per square inchChrect Overing Environmental Protection:0.000.0 pounds per square inchMaximum Operating Pressure:0.438 inches 1st endSect Angle:0.7.0 degrees 1st endHydrostatic Test Pressure:0.300.0 pounds per square inchCorrosion resistantVacuum In Torr:0.38Inside Surface Condition:SmothMeasuring Method And Length:7.000 inches workingSpecial Features:	
Outside Diameter: 0.343 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outside dormsion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Threaded Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Cuter Covering Environmental Protection: Corsion resistant Yacuum In Torr: 30.8 Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working	
0.343 inches Minimul Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Layer Composition And Location: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Corrosion resistant Hydrostatic Test Pressure: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Corrosion resistant Vacuum In Torr: 30.3 Burst Test Condition: Smooth Measuring Method And Length: 7.000 inches working	
Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximu Operating Pressure: 1300.0 pounds per square inch Layer Composition And Location: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 0.4000.0 pounds per square inch Corrosion resistant Vacuum In Torr: 30.0 pounds per square inch Corrosion resistant Vacuum In Torr: 30.8 Inside Surface Condition: Smoth Measuring Method And Length: 7.000 inches working	
2.000 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Stread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Stread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Stread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Stread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Stread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Stread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Stread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Stread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Corrosion resistant Features: 300.0 pounds per square inch Stread Size: 0.438 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Corrosion resistant Features: 50.8 Stread Size:	
Connection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provide:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchCuter covering Environmental Protection:Corrosion resistantSoatInside Surface Condition:So.8SmoothMeasuring Method And Length:7.000 inches workingSpecial Features:	
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Corrosion resistant Purforstatic Test Pressure: 3000.0 pounds per square inch Mydrostatic Test Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Hydrostatic Test Pressure: Stat Angle:	
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Corrosion resistant Puer Covering Environmental Protection: Corrosion resistant Yacuum In Tor: 50.8 Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working Special Features:	
Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Corrosion resistant Part Covering Environmental Protection: Corrosion resistant Yacuum In Torr: 50.8 Inside Surface Condition: Smoth Measuring Method And Length: 7.000 inches working Special Features:	
Connection Type:Threaded internal tube 1st endFeatures Provided:Electrostatic discharge capabilityBurst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchChread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchCorrosion resistantPrediction Covering Environmental Protection:Corrosion resistantSo.8Inside Surface Condition:SmothMeasuring Method And Length:7.000 inches workingSpecial Features:	-
Threaded internal tube 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smoth Mesuring Method And Length: 7.000 inches working	
Features Provided:Electrostatic discharge capabilityBurst Test Pressure:1200.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmothMessuring Method And Length:7.000 inches workingSpecial Features:	
Electrostatic discharge capability Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Uter Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working	
Burst Test Pressure:12000.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaxinum Operating Pressure:1500.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:7.000 inches workingSpecial Features:	
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working Special Features:	
Layer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:7.000 inches workingSpecial Features:	
Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:7.000 inches workingSpecial Features:	
Maximum Operating Pressure:1500.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:7.000 inches workingSpecial Features:	
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working Special Features:	
Thread Size:0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:7.000 inches workingSpecial Features:	
0.438 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:7.000 inches workingSpecial Features:	
Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working Special Features:	
37.0 degrees 1st endHydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:7.000 inches workingSpecial Features:	
Hydrostatic Test Pressure:3000.0 pounds per square inchOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:7.000 inches workingSpecial Features:	-
3000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working Special Features:	-
Outer Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:7.000 inches workingSpecial Features:	
Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working Special Features:	
Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working Special Features:	-
50.8 Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working Special Features:	
Inside Surface Condition: Smooth Measuring Method And Length: 7.000 inches working Special Features:	
Smooth Measuring Method And Length: 7.000 inches working Special Features:	
Measuring Method And Length: 7.000 inches working Special Features:	
7.000 inches working Special Features:	
Special Features:	
W/polyvinyl chloride acetate cover	
	W/polyvinyl chloride acetate cover

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0