## NSN 4720-00-771-3098

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-771-3098

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 1.125 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response                                   |
| Outside Diameter:   |
| 1.344 inches  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Features Provided:  |
| Electrostatic discharge capability  |
| Thready Qty Per Inch (tpi):   |
| 12 1st end  |
| Burst Test Pressure:  |
| 4000.0 pounds per square inch   |
| Layer Composition And Location:   |
| 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure:   |
| 1000.0 pounds per square inch   |
| Thread Size:  |
| 1.625 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 2000.0 pounds per square inch   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 48.000 inches working   |
| Special Features:   |
| Bonded asbestos external support  |
| Thread Series Designator:   |

Un 1st end

## NSN 4720-00-771-3098

Nonmetallic Hose Assembly - Page 2 of 2



| _ |    |      |   |      |
|---|----|------|---|------|
| c | hο | JIF. |   | ife: |
| J |    |      | _ | HG.  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0