

View Online at <https://aerobasegroup.com/nsn/4720-00-771-9428>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.380 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.840 inches

**Minimum Inside Bending Radius:**

5.000 inches

**Features Provided:**

Nonskive

**Burst Test Pressure:**

18000.0 pounds per square inch single response

**Layer Composition And Location:**

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

4500.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

9000.0 pounds per square inch single response

**Inside Surface Condition:**

Smooth

**Material:**

Rubber synthetic tube

**Media For Which Designed:**

Hydraulic fluid single response

**Specification Data:**

81343-sae100r9a government standard

**Specification Or Standard:**

1 class and 32 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541z0

**Mil-std (military Standard):**

Mil-h-24135 spec.