## NSN 4720-00-773-2849

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-773-2849

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.620 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
Hose Or Tubing Specification/std Data:
Sae j517, 100r2, type at-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Gasket seal / optional end 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting dichromate 1st end
Connection Type:
Threaded internal boss 1st end
Thready Qty Per Inch (tpi):
27 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
20000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
2nd layer braided steel wire
Maximum Operating Pressure:
5000.0 pounds per square inch

0.500 inches 1st end

Thread Size:

## NSN 4720-00-773-2849

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
10000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
300.000 inches
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Uns 1st end
Specification Data:
Sae j517, 100r2, type at-81343 national std/spec
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0