## NSN 4720-00-775-1492

Shelf Life:

N/a

Nonmetallic Hose Assembly - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/4720-00-775-1492  |
|--|
| Cross Sectional Shape:   |
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| nside Diameter:  |
| 0.312 inches   |
| Tempurature Rating:  |
| 65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response   |
| Outside Diameter:  |
| 0.562 inches   |
| Minimum Inside Bending Radius:   |
| 5.000 inches   |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Features Provided:   |
| Electrostatic discharge capability   |
| Burst Test Pressure:   |
| 14000.0 pounds per square inch   |
| Layer Composition And Location:  |
| 1st layer spirally laid steel wire and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant |
| steel wire   |
| Maximum Operating Pressure:  |
| 3000.0 pounds per square inch  |
| Thread Size:   |
| 0.562 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Hydrostatic Test Pressure:   |
| 6000.0 pounds per square inch  |
| nside Surface Condition:   |
| Smooth   |
| Measuring Method And Length:   |
| 36.000 inches working  |
| Thread Series Designator:  |
| Jnf 1st end  |

## NSN 4720-00-775-1492

Nonmetallic Hose Assembly - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A542a0