

View Online at <https://aerobasegroup.com/nsn/4720-00-777-0419>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-65.0 degrees fahrenheit and 165.0 degrees fahrenheit single response

Outside Diameter:

0.781 inches

Minimum Inside Bending Radius:

6.000 inches

Quick Disconnect Size:

0.500 inches 2nd end

Connection Style:

Push (internal) 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external pipe 1st end

Burst Test Pressure:

750.0 pounds per square inch

Layer Composition And Location:

1st layer braided fabric and outer layer molded rubber, synthetic

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

250.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and cold resistant and hydraulic solution resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

16.750 inches

Media For Which Designed:

Air and hydraulic fluid, silicate-ester base single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0