NSN 4720-00-779-7624

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-779-7624

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.875 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.094 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Burst Test Pressure: |
| 5000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1250.0 pounds per square inch |
| Thread Size: |
| 1.312 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 2500.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 21.000 inches working |
| Thread Series Designator: |
| Un 1st end |
| Shelf Life: |

N/a

NSN 4720-00-779-7624

Nonmetallic Hose Assembly - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A542a0