NSN 4720-00-782-1422

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-782-1422

| Cross Sectional Shape: | | | | |
|---|--|--|--|--|
| Round | | | | |
| Thread Class: | | | | |
| 3b 2nd end | | | | |
| Thread Direction: | | | | |
| Right-hand 1st end | | | | |
| Inside Diameter: | | | | |
| 0.187 inches | | | | |
| Tempurature Rating: | | | | |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response | | | | |
| Outside Diameter: | | | | |
| 0.312 inches | | | | |
| Connection Style: | | | | |
| Swivel nut flare 2nd end | | | | |
| End Connection Design: | | | | |
| Elbow 1st end | | | | |
| Connection Type: | | | | |
| Threaded internal tube 2nd end | | | | |
| Thready Qty Per Inch (tpi): | | | | |
| 20 2nd end | | | | |
| Burst Test Pressure: | | | | |
| 12000.0 pounds per square inch | | | | |
| Layer Composition And Location: | | | | |
| Outer layer braided corrosion resistant steel wire | | | | |
| Maximum Operating Pressure: | | | | |
| 1500.0 pounds per square inch | | | | |
| Thread Size: | | | | |
| 0.438 inches 2nd end | | | | |
| Seat Angle: | | | | |
| 37.0 degrees 2nd end | | | | |
| Hydrostatic Test Pressure: | | | | |
| 3000.0 pounds per square inch | | | | |
| Flow Angle: | | | | |
| 90.0 degrees 1st end | | | | |
| Inside Surface Condition: | | | | |
| Smooth | | | | |
| Measuring Method And Length: | | | | |
| 25.200 inches working | | | | |
| Thread Series Designator: | | | | |
| Unf 2nd end | | | | |
| Shelf Life: | | | | |

NSN 4720-00-782-1422

Nonmetallic Hose Assembly - Page 2 of 2



| ш | Inıŧ | · / 1+ | Measure | |
|---|------|--------|---------|--|
| | | | | |

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.