NSN 4720-00-786-2991

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-786-2991

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.219 inches
Minimum Inside Bending Radius:
3.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
14 1st end
Burst Test Pressure:
1600.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
400.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
800.0 pounds per square inch
Outer Covering Environmental Protection:
Cold resistant and mildew resistant and oil resistant
Inside Surface Condition:
Smooth

NSN 4720-00-786-2991

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 36.750 inches Media For Which Designed: Air and fuel/oil, hydrocarbon single response Thread Series Designator: Uns 1st end Shelf Life: N/a Unit Of Measure: -Demilitarization: No

Fiig: A542a0