Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-787-8660

| Cross S | ectional Shape: |
|-----------|---|
| Round | |
| Thread | Class: |
| 3b 1st ei | nd |
| Thread | Direction: |
| Right-ha | nd 1st end |
| Inside D | Diameter: |
| 0.212 in | ches |
| Tempur | ature Rating: |
| -65.0 de | grees fahrenheit and 400.0 degrees fahrenheit single response |
| Outside | Diameter: |
| 0.250 in | ches |
| Minimu | m Inside Bending Radius: |
| 3.000 in | ches |
| Connec | tion Style: |
| Swivel n | ut, flareless 2nd end |
| End Cor | nnection Design: |
| Straight | 1st end |
| Connec | tion Type: |
| Threade | d internal tube 1st end |
| Feature | s Provided: |
| Electros | tatic discharge capability |
| Burst Te | est Pressure: |
| 12000.0 | pounds per square inch |
| - | omposition And Location: |
| | braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire |
| | m Operating Pressure: |
| - | oounds per square inch |
| Thread | |
| | ches 1st end |
| Seat An | - |
| - | prees 2nd end |
| - | atic Test Pressure: |
| - | oounds per square inch |
| Flow An | - |
| - | prees 2nd end |
| | overing Environmental Protection: |
| | n resistant and corrosion resistant and weatherproof |
| | surface Condition: |
| Smooth | |
| | ng Method And Length: |
| 21.000 ii | nches working |

NSN 4720-00-787-8660

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unjf 1st end

Specification Data:

81343-as623 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0