Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-788-5956
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.906 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
14 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:

**Inside Surface Condition:** 

Smooth

Measuring Method And Length:

35.844 inches excluding end fittings



Media For Which Designed:

Fuel/oil, hydrocarbon single response

## Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A542a0