## NSN 4720-00-789-6582

**Cross Sectional Shape:** 

Round

Thread Class: 2b 1st end

Un 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-789-6582

Inside Diameter:						
1.000 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response						
Outside Diameter:						
1.500 inches						
Minimum Inside Bending Radius:						
12.000 inches						
Connection Style:						
Swivel nut flare 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Thready Qty Per Inch (tpi):						
12 1st end						
Burst Test Pressure:						
4000.0 pounds per square inch						
Layer Composition And Location:						
1st layer braided steel wire and outer layer molded rubber, synthetic						
Maximum Operating Pressure:						
1000.0 pounds per square inch						
Thread Size:						
1.312 inches 1st end						
Seat Angle:						
37.0 degrees 1st end						
Outer Covering Environmental Protection:						
Cold resistant and oil resistant and water resistant						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
28.375 inches						
Media For Which Designed:						
Air and hydraulic fluid and fuel/oil, hydrocarbon and water single response						
Thread Series Designator:						

## NSN 4720-00-789-6582

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0