## NSN 4720-00-790-8103

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-790-8103



**Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.212 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** Between 0.360 inches and 0.390 inches **Minimum Inside Bending Radius:** 1.500 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Outer Covering Environmental Protection:** Corrosion resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 30.000 inches **Thread Series Designator:** Unjf 1st end

## NSN 4720-00-790-8103

Nonmetallic Hose Assembly - Page 2 of 2



| Spec | ifica | ation | Data: |
|------|-------|-------|-------|
|------|-------|-------|-------|

81343-as153 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0