Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-792-8318

Cross Sectional Shape: Round Thread Class: 1a 2nd end Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: 40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.969 inches Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Thread dexternal pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid stele wire and 2nd layer spirally laid stele wire and outer layer molded rubber Maximum Operating Pressure: 030.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 0.750 upounds per square inch Thread Size: 0.750 upounds per square inch Hydrostatic Test Pressure: 0.750 upounds per square inch Uter vere
Tread Class: 1a 2nd end Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.969 inches Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 350.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Hydrostatic Test Pressure: Fuel resistant and oil resistant
la 2nd end Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.969 inches Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.969 inches Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 700.0 pounds per square inch Hydrostatic Test Pressure: 700.0 pounds per square inch Hydrostatic Test Pressure: 700.0 pounds per square inch Hydrostatic Test Pressure: 700.0 pounds per square inch
Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.969 inches Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3050.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure:
Inside Diameter: Union U
0.500 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.969 inches Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximun Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 700.0 pounds per square inch Hydrostatic Test Pressure:
Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.969 inches Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Hread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 0.750 inches 2nd end Hydrostatic Test Pressure: 0.700.0 pounds per square inch Uter Covering Environmental Protection: Pressistant and oil resistant
 -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.969 inches Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Urread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 1400.0 pounds per square inch Urread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 1400.0 pounds per square inch Urread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 1400.0 pounds per square inch Uter Covering Environmental Protection: Fuel resistant and oil resistant
Outside Diameter: 0.969 inches Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
0.969 inches Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch
Connection Style: Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Plain 1st end End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch
End Connection Design: Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Straight 2nd end Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Connection Type: Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Threaded external pipe 1st end Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Features Provided: Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Electrostatic discharge capability Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
14000.0 pounds per square inch Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Layer Composition And Location: 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and outer layer molded rubber Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Maximum Operating Pressure: 3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
3500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Thread Size: 0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
0.750 inches 2nd end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
7000.0 pounds per square inch Outer Covering Environmental Protection: Fuel resistant and oil resistant
Outer Covering Environmental Protection: Fuel resistant and oil resistant
Fuel resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.000 inches
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:

NSN 4720-00-792-8318

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

