Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-793-6215

Cre	oss Sectional Shape:
	und
Th	read Class:
3b	1st end
Th	read Direction:
	ght-hand 1st end
	side Diameter:
0.1	88 inches
Те	mpurature Rating:
	5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
	itside Diameter:
0.3	12 inches
Co	nnection Style:
	rivel nut flare 1st end
	d Connection Design:
	aight 1st end
	nnection Type:
	readed internal tube 1st end
Fe	atures Provided:
Ele	ectrostatic discharge capability
Bu	rst Test Pressure:
12	000.0 pounds per square inch
La	yer Composition And Location:
Ou	ter layer braided corrosion resistant steel wire
Ма	ximum Operating Pressure:
15	00.0 pounds per square inch
Th	read Size:
0.4	38 inches 1st end
Se	at Angle:
37.	0 degrees 1st end
Hy	drostatic Test Pressure:
300	00.0 pounds per square inch
Ins	side Surface Condition:
Sm	nooth
Ме	easuring Method And Length:
30.	500 inches working
Th	read Series Designator:
Un	f 1st end
Sh	elf Life:
N/a	a
Un	it Of Measure:

## NSN 4720-00-793-6215

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

