

View Online at <https://aerobasegroup.com/nsn/4720-00-795-5073>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded external tube 2nd end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Not identical

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber

Thread Size:

0.500 inches 1st end

Seat Angle:

45.0 degrees 2nd end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic; external support consists of spring guard

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0