

View Online at <https://aerobasegroup.com/nsn/4720-00-795-5703>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.335 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.703 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

1st layer braided synthetic cord and outer layer molded rubber, synthetic

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Flow Angle:

120.0 degrees 1st end

Outer Covering Environmental Protection:

Cold resistant and hydraulic solution resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

53.500 inches

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0