Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-796-3823

Cross Sectional Shape:
Round
Thread Class:
3a 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.684 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Plain optional end 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal pipe 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.000 inches
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:

NSN 4720-00-796-3823

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

