NSN 4720-00-797-6174

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-797-6174

Cross Sectional Shape:
Round
Thread Class:
3b and 3a 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.125 inches
Tempurature Rating:
-64.0 degrees fahrenheit single response
Outside Diameter:
0.490 inches
Hose Or Tubing Specification/std Data:
Sae j1401-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting cadmium 1st end
Connection Type:
Threaded internal and external tube 2nd end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
3000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer molded rubber, synthetic
Thread Size:
0.375 inches and 0.625 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Outer Covering Environmental Protection:
Cold resistant and ozone resistant and water resistant and salt water resistant
Inside Surface Condition:
Smooth

20.000 inches

Measuring Method And Length:

NSN 4720-00-797-6174

Nonmetallic Hose Assembly - Page 2 of 2



Second End Swivel Action Capability: Not included Special Features: Inner conveying tube material-rubber, synthetic Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Unf and unf 2nd end Specification Data: Sae j1401-81343 national std/spec Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A542a0