NSN 4720-00-797-7755

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-797-7755

0.298 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response				
Outside Diameter:				
Between 0.455 inches and 0.490 inches				
Minimum Inside Bending Radius:				
2.500 inches				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Electrostatic discharge capability and reusable end fittings				
Burst Test Pressure:				
14000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
3000.0 pounds per square inch				
Thread Size:				
0.562 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
6000.0 pounds per square inch				
Outer Covering Environmental Protection:				
Corrosion resistant and fuel resistant and oil resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
19.125 inches working				
Thread Series Designator:				
Unjf 1st end				

NSN 4720-00-797-7755

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81343-as153 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0