NSN 4720-00-798-4202

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-798-4202

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.312 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.438 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| First End Fitting Specification/std Data: |
| Mil ms27053 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Second End Fitting Specification/std Data: |
| Mil ms27059 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Nut stainless steel 1st end |
| Fitting Component And Surface Treatment: |
| Nut passivate 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 18 1st end |
| Second End Relationship With First End: |
| Not identical |
| Burst Test Pressure: |
| 9000.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |

0.562 inches 1st end

NSN 4720-00-798-4202

Nonmetallic Hose Assembly - Page 2 of 2



| Seat Angle: |
|--|
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Flow Angle: |
| 45.0 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Abrasion resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 29.000 inches working |
| Second End Swivel Action Capability: |
| Not included |
| Special Features: |
| Inner conveying tube material-plastic, polytetrafluoroethylene; hose covered w/chafing guard |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unf 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |
| |