NSN 4720-00-799-3598

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-799-3598

Cross Sectional Shape:						
Round						
Thread Class:						
2b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.688 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response						
Outside Diameter:						
0.938 inches						
Minimum Inside Bending Radius:						
4.500 inches						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Thready Qty Per Inch (tpi):						
12 2nd end						
Burst Test Pressure:						
3750.0 pounds per square inch						
Layer Composition And Location:						
1st layer braided steel wire and outer layer braided steel wire						
Maximum Operating Pressure:						
1000.0 pounds per square inch						
Thread Size:						
1.062 inches 2nd end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
2000.0 pounds per square inch						
Flow Angle:						
45.0 degrees 2nd end						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
29.750 inches working						
Media For Which Designed:						

Air single response

NSN 4720-00-799-3598

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0