

View Online at <https://aerobasegroup.com/nsn/4720-00-799-9147>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.688 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Outside Diameter:

0.938 inches

Minimum Inside Bending Radius:

4.500 inches

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

3750.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.062 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.500 inches working

Thread Series Designator:

Unj 2nd end

Fsc Application Data:

Hose assembly, nonmetallic, except fire fighting

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0