NSN 4720-00-799-9147

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-799-9147

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.688 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
0.938 inches
Minimum Inside Bending Radius:
4.500 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
3750.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.500 inches working
Thread Series Designator:
Unj 2nd end

NSN 4720-00-799-9147

Nonmetallic Hose Assembly - Page 2 of 2



Fsc Application Dat

Hose assembly, nonmetallic, except fire fighting

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0