NSN 4720-00-800-3835

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-800-3835

One of Operational Observation
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response
Outside Diameter:
Between 0.453 inches and 0.500 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
Aircraft, hercules c-130
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1250.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:

30.000 inches working

NSN 4720-00-800-3835

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator
--------	--------	------------

Unjf 1st end

Specification Data:

88044-an6270 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0