## NSN 4720-00-800-8742

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-800-8742

Cross Costional Change
Cross Sectional Shape:
Round
Thread Class:
2b and 2a 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.125 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
5.000 inches
Exterior Color:
Black
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal and external tube 2nd end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided fabric and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.500 inches
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

## NSN 4720-00-800-8742

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0