NSN 4720-00-803-3860

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-803-3860

Cross Sectional Shape:					
Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.250 inches					
Outside Diameter:					
0.500 inches					
Connection Style: Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
1250.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided cotton cord and outer layer molded rubber, synthetic					
Maximum Operating Pressure:					
200.0 pounds per square inch					
Thread Size:					
0.438 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
400.0 pounds per square inch					
Outer Covering Environmental Protection:					
Abrasion resistant and fuel resistant and oil resistant					
Vacuum In Torr:					
254.0					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
5.625 inches working					
Media For Which Designed:					
Air single response					
Thread Series Designator:					
Unf 1st end					
Specification Data:					

88044-an6270 government standard

NSN 4720-00-803-3860

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0