

View Online at <https://aerobasegroup.com/nsn/4720-00-804-2652>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response

Outside Diameter:

1.234 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

3200.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

800.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Fuel resistant and hydraulic solution resistant and mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

8.500 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Specification Data:

96906-ms28741 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0