NSN 4720-00-805-0526

Nonmetallic Hose - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-805-0526

| Cross Sectional Shape: |
|---|
| Round |
| Inside Diameter: |
| Between 0.480 inches and 0.508 inches |
| Tempurature Rating: |
| -60.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| Between 0.906 inches and 0.968 inches |
| Minimum Inside Bending Radius: |
| 3.750 inches |
| Exterior Color: |
| Black |
| Burst Test Pressure: |
| 1000.0 pounds per square inch single response |
| Layer Composition And Location: |
| 1st layer braided synthetic cord err-100 |
| Maximum Operating Pressure: |
| 225.0 pounds per square inch single response |
| Hydrostatic Test Pressure: |
| 450.0 pounds per square inch single response |
| Outer Covering Environmental Protection: |
| Abrasion resistant and mildew resistant and oil resistant and ozone resistant |
| Vacuum In Torr: |
| 101.0 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 84.000 inches |
| Material: |
| Rubber synthetic tube |
| Media For Which Designed: |
| Air single response |
| Specification Data: |
| 81349-mil-h-3992 government specification |
| Specification Or Standard: |
| 2 type and a style |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

No

NSN 4720-00-805-0526

Nonmetallic Hose - Page 2 of 2

Fiig: A541z0

Mil-std (military Standard):

Mil-h-3992 spec.

