Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-805-2151

ross Sectional Shape:
ound
hread Class:
b 1st end
hread Direction:
ight-hand 1st end
nside Diameter:
187 inches
empurature Rating:
0.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
onnection Style:
wivel nut flare 1st end
nd Connection Design:
traight 2nd end
onnection Type:
hreaded internal tube 1st end
hready Qty Per Inch (tpi):
7 2nd end
urst Test Pressure:
000.0 pounds per square inch
ayer Composition And Location:
st layer rubber impregnated fabric and outer layer molded rubber, synthe
laximum Operating Pressure:
00.0 pounds per square inch
hread Size:
438 inches 1st end
eat Angle:
5.0 degrees 1st end
ydrostatic Test Pressure:
- 000.0 pounds per square inch
nside Surface Condition:
mooth
leasuring Method And Length:
.500 inches
ledia For Which Designed:
uel/oil, hydrocarbon single response
hread Series Designator:
nf 1st end
helf Life:
/a
nit Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

