

View Online at <https://aerobasegroup.com/nsn/4720-00-805-7445>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.688 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Connection Style:**

Inverted flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external pipe 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

20000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided wire and 2nd layer braided wire and 3rd layer braided cotton cord and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

5000.0 pounds per square inch

**Thread Size:**

0.250 inches 1st end

**Seat Angle:**

30.0 degrees 1st end

**Outer Covering Environmental Protection:**

Abrasion resistant and water resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

55.000 inches

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Nptf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0