NSN 4720-00-806-1133

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-806-1133

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.500 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
2.250 inches
Minimum Inside Bending Radius:
20.000 inches
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Thready Qty Per Inch (tpi):
11-1/2 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
1.500 inches 1st end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Outer Covering Environmental Protection:
Cold resistant and mildew resistant and oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Shelf Life:
A1/-

N/a

NSN 4720-00-806-1133

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0